



Europäisches Patentamt
European Patent Office
Office européen des brevets



EP 1 321 274 A1

EUROPEAN PATENT APPLICATION

(43) Date of publication:
25.06.2003 Bulletin 2003/26

(51) Int Cl.7: **B29C 45/27**

(21) Application number: 02026667.2

(22) Date of filing: 29.11.2002

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE SK TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:

- **Bazzo, Maurizio**
31010 Ormelle (Treviso) (IT)
- **Trevisiol, Nico**
31052 Maserada sul Piave (Treviso) (IT)

(30) Priority: 21.12.2001 IT TO20011214


**(74) Representative: Buzzi, Franco et al
c/o Buzzi, Notaro & Antonielli d'Oulx
Via Maria Vittoria 18
10123 Torino (IT)**

(71) Applicant: INCOS S.p.A
31020 San Polo di Piave (Treviso) (IT)

(54) Injection nozzle for plastic injection moulding equipment

(57) An injection nozzle for plastic injection moulding equipment having a nozzle tip (4) with an internal hollow element (5) made of a material with high thermal conductivity, and an external hollow element (6) made of a material with a lower thermal conductivity. The in-

ternal hollow element (5) is connected to the body (1) of the injector nozzle independently with respect to the external hollow element (6), and a space of mutual separation (19) is defined between the internal and external hollow elements (5,6).



Description

[0001] The present invention relates to plastic injection moulding equipment in general and, more in particular, an injection nozzle for such equipment, of the type comprising a body with a central passageway and a nozzle tip including an internal hollow element made of a material with high thermal conductivity and an external hollow element made of a material with a lower thermal conductivity.

[0002] An injection nozzle of this type is described and illustrated, for example, in European Patent EP-B-0633118 in the name of GELLERT, according to which the external hollow element presents a thread at one end that can engage with a corresponding thread on the injector body and, at the other end, a part providing sealed contact with the injection mould to which the injector is operatively associated. The internal hollow element is placed between the said central passageway and the external hollow element.

[0003] In the injector nozzle described in EP-B-0633118, the internal hollow element is locked and restrained relative to the body of the injector nozzle by the same external hollow element itself, which thus functions as an axial stop device for the internal hollow element. With this device, the external hollow element is in direct contact with the internal hollow element along wide areas of its surface, with the consequent transmission of a significant amount of heat due to conduction. Heat is thus transmitted from the internal hollow element, through the sealed contact part between the external hollow element and the injection mould to which the injection nozzle is applied, to the mould itself, which constitutes an undesired effect. Instead, it is desirable to reduce such heat transmission as much as possible for the efficiency of the injection moulding process.

[0004] In order to achieve this object, the subject of the invention is an injection nozzle of the type defined at the beginning, the essential characteristic of which resides in the fact that the internal hollow element is connected to the body of the injector independently of the external hollow element, and in the fact that a space of mutual separation is defined between the said external hollow element and the said internal hollow element.

[0005] The space of mutual separation provides an air gap, due to which there is no direct contact between the internal hollow element and the external hollow element and hence the transmission of heat from the injection nozzle to the mould is considerably reduced.

[0006] In accordance with a preferred form of embodiment of the invention, the internal hollow element is provided with a thread that engages with a corresponding thread on the body of the injector. In addition, the contact part of the external hollow element, which can beneficially be elastically sprung, has advantageously a substantially spherical surface and, between this contact part and the remainder of the external hollow element, a reduced-section annular part, which also contributes

to reducing the transmission of heat to mould, can be provided to advantage.

[0007] Further characteristics and advantages of the invention will become evident in the course of the detailed description that follows, with reference to the enclosed drawing, provided purely by way of a non-limitative example, which illustrates, in partial longitudinal section and in enlarged scale, the terminal part of an injection nozzle in accordance with the invention for plastic injection moulding equipment.

[0008] The injection nozzle represented in the drawing is, taken as a whole, of the generally known type and will therefore not be discussed in detail. For the purposes of the invention, it is sufficient to explain that this injector nozzle, corresponding to that described and illustrated in European patent application n° 01830680.3 in the name of A.S. (unpublished at the priority date of this application) for example, is inserted through the space S of a mould M for plastic injection, the cavity of which communicates with the space S through an injection duct D. The injection nozzle presents a body 1 with a central axial passageway 2 for the plastic material to be injected, aligned with the injection duct D and inside which a plug 3 can move axially, cooperating with the injection duct D as a shutter.

[0009] On the part of the injection nozzle 1 facing the injection duct D of the mould M, there is a nozzle tip 4 formed by an internal hollow element 5 made of a material with high thermal conductivity (typically copper) and an external hollow element 6 made of a material with a lower thermal conductivity, such as steel or titanium for example.

[0010] In accordance with a fundamental characteristic of the invention, the internal hollow element 5 and the external hollow element 6 are fixed to the body 1 of the injector nozzle separately and independently of each other, without any mutually direct contact.

[0011] More in detail, the internal hollow element 5 presents an axially internal portion 7 with an external thread 8 screwed into a corresponding thread 9 on the body 1 of the injector nozzle, and an axially external portion 10 that extends beyond the external hollow element 6 and through which the free end of the plug 3 moves. The internal hollow element 5 presents a thicker intermediate portion 11 between the axial portions 7 and 10, and the external surface of the axial portion 10 is conveniently curved.

[0012] In turn, the external hollow element 6 presents an axially internal portion 12 with an internal thread 13 screwed onto a corresponding external thread 14 on the body 1 of the injector nozzle, and an axially external portion 15. The external hollow element 6 has an intermediate portion of greater thickness 16 between the axially internal portion 12 and axially external portion 15, and the axially external portion 15 connects to the intermediate portion 16 via a flattened portion 17.

[0013] The axially external portion 15 can be beneficially made to be elastically sprung, such as in the case

where the external hollow element 6 is made from spring steel for example, and presents a generally spherical external surface 18, in substantially linear peripheral contact with the mould M. This ensures an efficient hermetic contact seal without the need for resorting to excessive machining tolerances.

[0014] As is clearly visible in the figure, there is no contact between the internal hollow element 5 and the external hollow element 6, and between the axially external 10 and intermediate 11 portions of the former on one side and the axially external 15 and intermediate 16 portions of the latter on the other, an annular air space 19 is defined, constituting a thermal insulation air space.

[0015] The above-described arrangement reduces the transfer of heat from the internal hollow element 10, or rather from the plastic material being injected when it flows through the central passageway 2 of the injector nozzle 1, and the external hollow element 16, or rather the mould M.

[0016] Experimental tests conducted by the applicant have demonstrated that with this arrangement, the temperature of the mould M in the zone of the contact surface 18 of the external annular element 6 is appreciably lower than in the case where conventional injector nozzles are used, where the internal and external hollow elements of the relative nozzle tip are arranged in mutual contact.

[0017] Naturally, the constructional details and forms of embodiment could be extensively changed with respect to that described and illustrated without leaving the scope of this invention, as is defined in the following claims.

Claims

1. An injection nozzle for plastic injection moulding equipment, including a body (1) with a central passageway (2) and a nozzle tip (4) including an internal hollow element (5) made of a material with high thermal conductivity and an external hollow element (6) made of a material with a lower thermal conductivity, wherein one end (12) of the said external hollow element (6) has a thread (13) that can engage with a corresponding thread (14) on the body (1) of the injector nozzle and, at the other end (15), a part providing sealed contact (18) with the injection mould (M), and wherein the internal hollow element (5) is positioned between the said central passageway (2) and the said external hollow element (6), **characterized in that** the internal hollow element (5) is connected to the body (1) of the injector nozzle independently with respect to the said external hollow element (6), and by the fact that a space of mutual separation (19) is defined between the said external hollow element and (6) the said internal hollow element (5).

2. An injector nozzle according to Claim 1, **characterized in that** the said internal hollow element (5) is provided with a thread (8) which engages with a corresponding thread (9) on the body (1) of the injector nozzle.

3. An injector nozzle according to Claim 2, **characterized in that** the said thread (13) of the external hollow element (6) is an internal thread and that the corresponding thread (14) on the body (1) is an external thread, while the said thread (8) of the internal hollow element (5) is an external thread and corresponding thread (9) on the body (1) is an internal thread.

4. An injector nozzle according to any of the Claims 1 to 3, **characterized in that** a reduced-section annular part (17) is provided between the said contact part (18) of the external hollow element (6) and the remainder (12 and 16) of the said external hollow element (6).

5. An injector nozzle according to any of the Claims 1 to 4, **characterized in that** the said contact part (18) of the external hollow element (6) has a substantially spherical surface.


6. An injector nozzle according to any of the preceding Claims, **characterized in that** the said contact part (18) of the external hollow element (6) is elastically sprung.

7. An injector nozzle according to any of the preceding Claims, **characterized in that** the said external hollow element (6) is made of steel.

8. An injector nozzle according to any of the Claims 1 to 6, **characterized in that** the said external hollow element (6) is made of titanium.

9. An injector nozzle according to any of the preceding Claims, **characterized in that** the said internal hollow element (5) and the said external hollow element (6) have respective, enlarged intermediate portions (11, 16).

10. An injector nozzle according to any of the preceding Claims, **characterized in that** the said internal hollow element (5) and the said external hollow element (6) have respective, curved surfaces that delimit, at least partially, said space of mutual separation (19).





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 02 6667

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 6 302 680 B1 (GELLERT JOBST ULRICH ET AL) 16 October 2001 (2001-10-16)	1	B29C45/27
Y	* column 3, line 14 - line 21 *	2-9	
	* column 3, line 41 - column 4, line 14 *		

X	US 5 492 467 A (HUME WILLIAM J ET AL) 20 February 1996 (1996-02-20)	1	
Y	* column 10, line 5 - line 50 *	2-9	

D,A	EP 0 633 118 A (GELLERT JOBST U) 11 January 1995 (1995-01-11)	1	
	* figures 2,3 *		
	* column 5, line 47 - column 6, line 10 *		
	* column 3, line 37 - column 4, line 53 *		

A	WO 01 28750 A (BABIN DENIS ;ZHUANG HELEN (CA); MOLD MASTERS LTD (CA)) 26 April 2001 (2001-04-26)	1	
	* page 4, line 2 - page 5, line 15 *		
	* page 6, line 28 - page 7, line 2 *		

A	EP 0 854 027 A (HUSKY INJECTION MOLDING) 22 July 1998 (1998-07-22)	1	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
	* figures 1-9 *		B29C

The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 14 March 2003	Examiner Alink, M
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03.02 (p4/c01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 02 6667

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14-03-2003

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 6302680	B1	16-10-2001	AU	2530600 A	04-09-2000
			BR	0010039 A	26-03-2002
			WO	0048814 A1	24-08-2000
			CN	1342113 T	27-03-2002
			EP	1152880 A1	14-11-2001
			JP	2002537142 T	05-11-2002

US 5492467	A	20-02-1996	US	5674439 A	07-10-1997

EP 0633118	A	11-01-1995	CA	2099454 A1	31-12-1994
			AT	170445 T	15-09-1998
			CN	1098675 A ,B	15-02-1995
			DE	4422065 A1	12-01-1995
			DE	69412931 D1	08-10-1998
			DE	69412931 T2	21-01-1999
			EP	0633118 A1	11-01-1995
			JP	7137079 A	30-05-1995

WO 0128750	A	26-04-2001	CA	2286953 A1	18-04-2001
			AU	7896800 A	30-04-2001
			WO	0128750 A1	26-04-2001

EP 0854027	A	22-07-1998	US	5879727 A	09-03-1999
			CA	2227085 A1	21-07-1998
			EP	0854027 A1	22-07-1998

EPO FORM P0159

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKewed/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.